# WHAT IS TARKETT'S LINO?

## AN UNCHANGED RECIPE SINCE 1898



Linseed oil: flax is the starting point. The crop's seeds are dried and pressed to yield linseed oil.

Pine rosin: added to the linseed oil, it creates the binding agent, called linoleum cement.

Wood flour: lends the mixture lightness and durability.

**Cork dust:** keeps it strong and flexible.

Calcium carbonate: a natural filler, to bring stability.

**Pigments:** for the rich colours!

and jute: the base of this most sustainable flooring material.

# A VERSATILE MATERIAL

Robust





Resistant to abrasion, stains and chemicals

Acoustic



Up to 18dB sound insulation

# Sustainable

Our xf<sup>2TM</sup>: surface treatment means an excellent resistance, a reduced life cycle cost, and a minimized impact on the environment



**Electricity**' \* Compared to linoleum without xf<sup>2TM</sup>

A unique offer on the market

#### Originale ► The first 100% natural linoleum,


Cradle to Cradle Gold certified™



## ▶ The only linoleum approved for use on walls

LinoWall xf<sup>2TM</sup>!

and featuring Bs2-d0 fire certification



Static control

► Stadic dissipative xf<sup>2™</sup> and Conductive xf<sup>2™</sup> options



Open up to a world of colour with 7 designs and 112 colours

A DESIGN PRODUCT



THE ULTIMATE FLOORING EXPERIENCE