

# ModularT 7 Chevron

hungarian chevron

LUXURY VINYL TILES

## Oak Origin Light Brown

Ref. 257021083 (left) / 257021084 (right)

## Oak Street Beige Stone

Ref. 257021087 (left) / 257021088 (right)

The **ModularT 7** collection is LVT based on the latest trends in ceramics and wooden flooring. Performance features such as simple maintenance, water resistance, durability and increased impact sound reduction make the ModularT 7 an excellent choice both functionally and aesthetically.

We have expanded the collection of 43 designs available in the format of panels and tiles with a new format – **a hungarian chevron**.

You can now order each of the wooden designs of the ModularT 7 collection in herringbone format. In order to guarantee the best possible service and delivery time, **the 4 designs presented in this brochure are kept in stock in Serbia for each color up to 230 m<sup>2</sup> (given value is for left and right chevron in total)**. Other wooden patterns from ModularT 7 collection can be produced in chevron format on request. For more information about special production, please ask Sales Representative.

## Oak Origin Nature

Ref. 257021085 (left) / 257021086 (right)

## Oak Street Grey

Ref. 257021089 (left) / 257021090 (right)

# ModularT 7 Chevron

LUXURY VINYL TILES

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Compact resilient floor covering
Domestic classification	EN ISO 10874	23
Commercial classification	EN ISO 10874	34
<b>Technical characteristics</b>		
Total thickness	EN ISO 24346	2.50 mm
Wear layer thickness	EN ISO 24340	0.70 mm
Total weight	EN ISO 23997	3200 g/m <sup>2</sup>
Abrasion (wear layer binder content)	EN ISO 10582	Type I
Surface treatment	–	X-treme
Beveling	–	4-sided micro bevel
Type of instalation	–	Glued
<b>Performance for CE marking</b>		
Declaration of Performance	EN 14041	2701-0060-DOP-2019-12
<b>Technical data</b>		
Dimensional stability	EN ISO 23999	Average measured value: ≤ 0.10%
Curl resultant to heat	EN ISO 23999	≤  2  mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Effect of furniture legs	EN ISO 16581	No damage
Effect of castor chair	EN ISO 4918	No damage
Acoustic insulation – ΔLw	EN ISO 717-2	6 dB
Thermal resistance	EN ISO 10456	≤ 0.03 m <sup>2</sup> •K/W
Light fastness	EN ISO 105-B02	≥ 7
Fungi and bacteria resistance	EN 846 part C	Do not support growth – no biocycles
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)
Electrostatic properties	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating	–	Suitable (max. 27°C)
<b>Environmental aspect</b>		
Recyclability	–	Yes
VOC emission	–	< 100 μg/m <sup>3</sup>
Phtalate	–	100% phtalate free
<b>Decors and dimensions</b>		
Planks	–	Plank 120 × 600 mm – 60 planks = 3.822 m <sup>2</sup> /box – 60 boxes/pallet
Available decors	–	4 designs available on stock
<b>Guarantee</b>		
Commercial guarantee	–	10 years

For questions about the product offer  
please contact your Tarkett sales representative.

[www.professionals.tarkett.com](http://www.professionals.tarkett.com) | [www.facebook.com/tarkettofficial](https://www.facebook.com/tarkettofficial)

